

X400

Bright and portable

- Bright XGA projector 4000 ANSI lumens
- Easy connectivity HDMI, VGA, USB-A Power, 2W speaker
- Low ownership costs up to 10,000 hours² lamp life
- Lightweight and portable























X400

Transform the delivery of your presentation with the first ever 4,000 lumen, small, lightweight X400 projector. This model is designed to be used at any time of day and for multiple purposes, including professional use - from business meetings to classrooms. It offers top quality projected colours, long lamp life with a low overall cost of ownership.

This product boasts simplicity in design, with easy navigation and reliability. Convenient, with multiple inputs including HDMI and MHL, this projector is ideal for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro enabling you to connect your laptop, PC or Bluray player. This compact model can either be installed or conveniently taken on the move.

High contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.

Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.

Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

MHL

Turn your projector into a smart display by connecting your smartphone or tablet with a single cable using MHL; now you can view presentations and documents, stream videos and share photos on the big screen. You can even use MHL to connect and power the HDCast Pro (sold separately).

Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

Energy saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

Quick resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy, the "Auto Power Off" feature automatically turns off the projector after a set period of time if it is not being used

Direct power off

You can powered off your projector immediately or directly at the mains. Should you require to turn you projector back on immediately it will take about 90 seconds to start up.

Long lamp life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.

Amazing colours

Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs. Perfect for a range of graphic and video presentations.





Wireless

Stream Full 1080p 3D content to your projector wirelessly; eliminating the hassle and extra cost of installing long cables, the WHD200 (sold separately) allows you to connect a Blu-ray[™] player, set-top box, gaming console or AV receiver instantly.

USB power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast

24/7 operation

Optoma projectors have been designed to operate 24 hours a day in

standard orientation. Perfect for applications where prolonged periods of use is required. Subject to 24 hour terms and conditions.

24/7 Operation - Standard lamp warranty applies. Projector warranty is based on standard business usage hours. For optimum performance Optoma recommends that your projector is turned off or placed in standby mode for 30 minutes every 24 hours to prolonging the life of your lamp.

Specification

Native Resolution XGA 1024 x 768 Brightness¹ (Bright Mode) 4000 ANSI Lumens Contrast 22,000:1 Lamp Life² Dynamic/EcoBright/Education cycle 6500/600005000/10000 (hrs) Throw Ratio 1,159 - 2.15:1 ZOO Type 1,1 MBMI (14 al 30 support) + MHL, VGA (YPBPr/RGB), Composite, Audio in 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (SV-1A) Speaker (Watts) 2W Keystone Correction ± 40° Vertical Weight (Kg) 2.5 Dimensions (W x D x H) (mm) 298 x 230 x 97 mm Aspect Ratio 4.3 Native, 165 Compatible Offset 115% Projection Distance 12 · 12m Projection Distance 15 · 10, WGA, UKSA, XSCA, XGA, SYCA, VGA, Mac Uniformity 75% Fibril 3.0 · 1 · 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	Display Technology	Single 0.55" XGA DC3 DMD chip DLP® Technology by Texas Instruments
Contrast 22,000:1 Lamp Life ² Dynamic/Eco/Bright/Education cycle 6500/6000/5000/10000 (hrs) Throw Ratio 1.95 - 215:1 Zoom Type 1.1x Manual I/O Connectors 2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (SV-1A) Speaker (Watts) 2W Keystone Correction ± 40° Vertical Weight (kg) 2.5 Dimensions (W x D x H) (mm) 298 x 230 x 97 mm Aspect Ratio 4.3 Native, 16.9 Compatible Offset 115% Projection Distance 12.1 2m Projection Distance 12.1 2m Projection Distance 12.1 2m Projection Compatibility 75% Computer Compatibility 75% Video Compatibility PAL (B, D, G, H, I, M, N, 4-33MHz), NTSC (M, J. 3.58MHz, 4.44MHz), SECAM (B, D, G, K, K1, L, 4.25MHz, 4.4MHz, 480l/p, 576l/p, 720p(6004hz), 1308(6004hz), 1308(6004hz		0, ,
Contrast 22,000:1 Lamp Life ² Dynamic/Eco/Bright/Education cycle 6500/6000/5000/10000 (hrs) Throw Ratio 1.95 - 215:1 Zoom Type 1.1x Manual I/O Connectors 2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (SV-1A) Speaker (Watts) 2W Keystone Correction ± 40° Vertical Weight (kg) 2.5 Dimensions (W x D x H) (mm) 298 x 230 x 97 mm Aspect Ratio 4.3 Native, 16.9 Compatible Offset 115% Projection Distance 12.1 2m Projection Distance 12.1 2m Projection Distance 12.1 2m Projection Compatibility 75% Computer Compatibility 75% Video Compatibility PAL (B, D, G, H, I, M, N, 4-33MHz), NTSC (M, J. 3.58MHz, 4.44MHz), SECAM (B, D, G, K, K1, L, 4.25MHz, 4.4MHz, 480l/p, 576l/p, 720p(6004hz), 1308(6004hz), 1308(6004hz	Brightness ¹ (Bright Mode)	4000 ANSI Lumens
Throw Ratio 1.95 - 2.15.1 Zoom Type 1.1x Manual I/O Connectors 2x HDMI (1.4a. 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (SV-1A) Speaker (Watts) 2W Keystone Correction ± 40° Vertical Weight (kg) 2.5 Dimensions (W x D x H) (mm) 299 x.230 x 97 mm Aspect Ratio 4.3 Native, 16:9 Compatible Offset 115% Projection Distance 115% Projection Distance 12. ± 12m Projection Lens F72.4 * 2.53; = 21.85 * 24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, VGA, Mac Video Compatibility FHD, HD, WXGA, WAS, WAS, WAS, WAS, WAS, WAS, WAS, WA		22,000:1
Throw Ratio 1.95 - 2.15.1 Zoom Type 1.1x Manual I/O Connectors 2x HDMI (1.4a. 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (SV-1A) Speaker (Watts) 2W Keystone Correction ± 40° Vertical Weight (kg) 2.5 Dimensions (W x D x H) (mm) 299 x.230 x 97 mm Aspect Ratio 4.3 Native, 16:9 Compatible Offset 115% Projection Distance 115% Projection Distance 12. ± 12m Projection Lens F72.4 * 2.53; = 21.85 * 24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, VGA, Mac Video Compatibility FHD, HD, WXGA, WAS, WAS, WAS, WAS, WAS, WAS, WAS, WA	Lamp Life ² Dynamic/Eco/Bright/Education cycle	6500/6000/5000/10000 (hrs)
1.1 k Manual		1.95 - 2.15:1
A power (5V-1A)		
A Power (SV-1A)	71	2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-
Keystone Correction ± 40° Vertical Weight (kg) 2.5 Dimensions (W x D x H) (mm) 298 x 230 x 97 mm Aspect Ratio 4.3 Native, 16.9 Compatible Offset 115% Projection Screen Size 0.71 - 7.73m (27.78° - 304.4°) Diagonal 4:3 Projection Lens 1.2 - 12m Projection Lens Ff.2.4~2.53; f=21.85~24.01mm Uniformity 75% Computer Compatibility PHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25.MHz, 4.40My, 576lp/, 720p(50/60Hz), 1080l(50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Voer-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby)		
Weight (kg) 2.5 Dimensions (W x D x H) (mm) 298 x 230 x 97 mm Aspect Ratio 4.3 Native, 16.9 Compatible Offset 115% Projection Screen Size 0.71 - 7.73m (27.78" - 304.4") Diagonal 4:3 Projection Distance 1.2 - 12m Projection Lens F12.4-2.53; f=21.85-24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H. I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 1080(p(24/50/60Hz)) 3D Support FINI 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsofts Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-typ-Side:1080615 (50, 720p6) 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4		2W
Dimensions (W x D x H) (mm) 298 x 230 x 97 mm		
Aspect Ratio Offset Of		
Offset 115% Projection Screen Size 0.71 - 7.73m (27.78" - 304.4") Diagonal 4:3 Projection Distance 1.2 - 12m Projection Lens F/2.4-2.53; (=21.85-24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25.MHz, 4.4MHz, 480l/p, 576l/p, 720p(50/600Hz), 1080l/6060Hz), 1		
Projection Screen Size 0.71 - 7.73m (27.78" - 304.4") Diagonal 4:3 Projection Lens 1.2 - 12m Projection Lens Fiz.4-2.53; f=21.85-24.01mm Uniformity 75% Computer Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.40MHz, 480l/p, 576l/p, 720p(5060Hz), 1080l(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Sider-1080l550 / 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Displayable Colours Moise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 260W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless		
Projection Distance 1.2 - 12m Projection Lens F72.4~2.53; Fe21.85~24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.44MHz, 480i/p, 576i/p, 720p(5060Hz), 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby)		
Projection Lens F/2.4~2.53; f=21.85~24.01mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.40Hz, 480l/p, 576l/p, 720p(50/60Hz), 1080p(24/50/60Hz) DSupport Full 3D - The 3D features of Optoma projector can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080050 / 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz / (120Hz for 3D) Displayable Colours Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security Max. Humidity 85%, Max. Altitude 3000m Security Security Again, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Mireless	Projection Screen Size	0.71 - 7.73m (27.78" - 304.4") Diagonal 4:3
Uniformity Computer Compatibility FHD, HN, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.40Hz, 480i/p, 576i/p, 720p(50/60Hz), 1080l(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24.4 -85Hz (19Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Mcrefess	Projection Distance	1.2 - 12m
Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless	Projection Lens	F/2.4~2.53; f=21.85~24.01mm
PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50)60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-19-Side-108ib(5) 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Power-Under: 1080p24, 720p50 / 60 Noise Level (Eco mode) Sightly Power Supply 1073.4 Million Noise Level (Eco mode) 29dB Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Wireless Yes	Uniformity	75%
S76i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Wireless Yes	Computer Compatibility	FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display Security bar, Kensington lock, password protection On Screen Display Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Wireless Yes	Video Compatibility	
Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Yes	3D Support	with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D
Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby)	3D Compatibility	Frame-pack: 1080p24, 720p50 / 60
Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Horizontal Scan Rate	15.3 - 91.1kHz
Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby)	Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, French, Italian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Displayable Colours	1073.4 Million
Power Consumption 266W Bright mode / 204W Eco mode (< 0.5W Standby) Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Noise Level (Eco mode)	29dB
Lamp Type 220W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Power Supply	100-240V, 50-60Hz
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Power Consumption	266W Bright mode / 204W Eco mode (< 0.5W Standby)
Security Se	Lamp Type	220W
On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card. Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Security	Security bar, Kensington lock, password protection
Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	On Screen Display	Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi,
Optional Wireless Yes	Standard Accessories	AC power cord, VGA cable, remote control, battery, quick start card.
	Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount
RoHS Compliant		Yes
	RoHS	Compliant



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

²Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

Copyright © 2017, Optoma Europe Limited. Optoma, NuForce and Nu are registered trademarks of Optoma Corporation. Optoma Europe Limited is the licensee of the registered trademarks. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images are for representation purposes only and may be simulated. All content on this site is protected by copyright.

Privacy Terms and conditions

Registered Office: 42 Caxton Way, Watford Business Park, Watford. WD18 8QZ . Registered No. 3399395

05/05/2017 13:15